## **Standard Equipment and Features**

- >> 2 Horse Power Motor
- >> 208/230 Volt
- >> Single or 3-Phase
- >> Gear-Reduction Transmission
- >> 30-Minute Timer with automatic shut-off
- » 3-Speed
- >> #12 Attachment Hub
- >> Stainless Steel Bowl Guard
- >> Manual Bowl Lift
- >> Bowl Lift Safety
- >> Dough Hook
- >> Wire Whip
- >> Beater/Paddle
- >> Stainless Steel Bowl
- >> Bowl Locking Handles
- >> Bowl Stabilizer
- >> Industry Leading, 3-Year Limited Parts Warranty
- >> 1-Year Full Parts and Labor Warranty

### **Optional Accessories**

- >> 40-quart Knockdown Plate
- >> 40-quart Bowl
- >> Whip, Beater, and Hook for 40-quart Bowl

Please specify when ordering mixer.

# **Built to Last... Priced to Save!**

Precision North America, Inc. 60 Commerce Ave. Albany, New York 12206










www.precisionmixers.com • Phone: 1-877-R-MIXERS (1-877-764-9377) • Fax: 518-462-3389



# **Specifications and Dimensions**







#### **Electrical:**

- 208/240 Volt
- 1 or 3-Phase Power
- Entela Approved

## Weight:

- 814 Pounds Net
- 940 Domestic Shipping

## Warranty:

- 3-Year Limited Parts, (Motor, Transmission, and Drive-Train)
- 1-Full Year Parts and Labor

## **Amp Draw Specifications**

Phase	Volts	Amps
1	208	16.9
1	240	14.7
3	208	7.5
3	240	6.5

#### **Dimensions**

## Mixer Body:

A: 30" Wide B: 59<sup>1</sup>/<sub>2</sub>" High C: 37" Depth

Bowl:

Outside w/handles: 24"

Inside: 18<sup>1</sup>/<sub>2</sub>" Height: 18<sup>1</sup>/<sub>4</sub>"

NOTE: Hub attachment not to be used while mixing

## **Benefits**

## Motor:

- Heavy Duty, 2-Horse Power
- Manual Reset Motor Overload

#### **Bowl Lift:**

• Locks in any position

#### **Bowl Stabilizer:**

• Flat Exterior Bowl Base for Bowl Stability

#### **Attachment Hub:**

• Uses standard # 12 attachments

#### Timer:

• Automatic shutoff at desired mixing time

Easy Maintenance and Service National Network of Service Professionals

## Safety features

#### **Bowl Guard:**

• Auto shut-off when bowl guard is opened.

#### Lift Safety:

• Auto shut-off when bowl is lowered.

Speed	Agitator RPMs	Attachment Hub RPM's
1	104	119
2	197	226
3	331	380

Specifications are subject to change.

Precision North America, Inc. 60 Commerce Ave. Albany, New York 12206





www.precisionmixers.com • Phone: 1-877-R-MIXERS (1-877-764-9377) • Fax: 518-462-3389