



ON DEMAND SEAL PLATE

SIGNIFICANTLY REDUCES ENERGY CONSUMPTION

FEATURES

- 115 Volt Power Supply
- Electronic Temperature Controlled Film Cut Off Rod
- 6" by 15" On-Demand Timer Controlled Heated Seal Plate That Significantly Reduces Power Consumption
- Seal Plate Reaches Seal Temperature Within Seconds
- Two Selectable Seal Times To Accommodate Different Film Types
- Thermostatic High Temperature Limit Device
- Thermistor Controlled Circuit That Reduces Power Consumption As Residual Heat Increases In Seal Plate
- Stainless Steel Base
- Aluminum And Stainless Steel Construction Throughout
- Stainless Steel Wrapping Surface
- Space Saving Design That Requires Less Counter Space
- 18" Maximum Roll Width
- 8" Maximum Roll Diameter
- Supplied With A Replaceable Non-Stick Cover to Maintain A Hygienic Seal Surface

MODEL SPECS

FILM CAPACITY	18"
HOT PLATE	6" x 15"
OVERALL DIMENSIONS	25" D, 23" W, 9" H (64 D, 59 W, 23 H cm)
POWER REQUIREMENT	115 Volt, 19 Amp, 60Hz 20A breaker, GFCI protected circuit compatible with NEMA 5-20P(shown) ⚠
WATTAGE	2200 Watts (Non Continuous)
WEIGHT	28 lbs.(12.7 kg)

